



EonStor GS Family

Enterprise-Class Unified Storage

Integrating SAN, NAS and Cloud



Highlight

- Consolidates SAN, NAS and Cloud in a single system to enjoy powerful storage features
- Automatically reconnected I/O during path failure
- Cache protection with super-capacitor and flash to ensure data safety
- IDR support ensures that all hard drives are healthy to prevent from rebuilding
- EonOne management interface provides a single control center for system management and resources monitoring

Introduction

The EonStor GS series forms the backbone of our high-performance enterprise storage solution with its powerful performance, flexibility, and high expandability helping to efficiently boost overall productivity. GS can handle large amounts of I/O and file transfers even under high workloads and are especially suitable for hybrid environments adopting SAN, NAS, and Cloud integration. It is perfect for those who want performance, capacity, and a high port count, and at the same time, it is ideal for budget-conscious applications as it can easily meet all general storage needs.

Symmetric Active-active Controllers

The EonStor GS Series supports symmetric active-active controller configuration for block-level data access to achieve little or no failover time in the event of a path failure.

This design is also able to minimize administrative efforts and boost operation efficiency. Hosts can access the same LUNs simultaneously via both controllers. I/O workloads are more evenly distributed across both controllers and all paths, effectively minimizing costly path management time.

Infinite Storage Capacity on Cloud

The key benefits of cloud storage solutions are their high service durability and the “scale on demand” flexibility allowing to expand storage as your business evolves. As a great on-premises cache/backup storage to cloud storage, EonCloud Gateway features both a wide range integration for both private cloud and public cloud solutions and smart data services such as heterogeneous cache modes, tiering and backup modes to automatically streamline the optimal data flow between local and cloud storage and also save costs.

Comprehensive Data Protection and Security

Security threats are not the only concern when it comes to safeguarding data. Unexpected disk failures, natural disasters, and power outages - all add up to the risk of data loss. EonStor GS series ensures that risk is minimal with its integrated backup functions such as Intelligent Drive Recovery (IDR), snapshot, local replication, remote replication, and file-level rsync.

PHYSICAL SPECIFICATIONS

Product Series		GS 1000 Gen2	GS 2000	GS 3000 Gen2	GS 4000 Gen2
Form Factor & Available Model	2U 12-bay	GS 1012 R2CF/S2CF	GS 2012 R/S GS 2012 RT/ST	GS 3012 R2CF/S2CF	GS 4012 R2CF/S2CF
	2U 24-bay	GS 1024 R2CBF/S2CBF	GS 2024 RB/SB GS 2024 RTB/STB	-	-
	2U 25-bay	-	-	GS 3025 R2CBF/S2CBF	GS 4025 R2CBF/S2CBF
	3U 16-bay	GS 1016 R2CF/S2CF	GS 2016 R/S GS 2016 RT/ST	GS 3016 R2CF/S2CF	GS 4016 R2CF/S2CF
	4U 24-bay	GS 1024 R2CF/S2CF	GS 2024 R/S GS 2024 RT/ST	GS 3024 R2CF/S2CF	GS 4024 R2CF/S2CF
	4U 60-bay	-	-	GS 3060 R2CLF/G2LF	GS 4060 R2CLF/G2LF
Note: G: Non upgradable single controller S: Upgradable single controller R: Redundant controller L: One drawer B: 2.5" Form factor 2: Gen2 C: Super capacitor F: Gateway					
Controller	Redundant or Upgradable single controller			Redundant or Non upgradable single controller or Upgradable single controller	
Cache Backup Techniques	Super capacitor+Flash module (Only for upgradable single controller and redundant controller models)				
CPU	Intel® Atom® 4 Core	Intel® Pentium® 2 or 4 core	Intel® Xeon® D 4 Core	Intel® Xeon® D 8 Core	
Cache Memory (per system)	Default DDR3 16GB Expandable up to 32GB	Default DDR4 16GB Expandable up to 128GB	Default DDR4 16GB Expandable up to 512GB		
Supported Drives	2.5" SAS or SATA SSD 2.5" 12Gb/s SAS 10,000 or 15,000 RPM HDD 3.5" 12Gb/s SAS 7,200 RPM HDD 3.5" 6Gb/s SATA 7,200 RPM HDD Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.				
Max. Drives Number (via expansion enclosure)	448	896	896	896	
Max. SSD Cache Pool	1TB	3.2TB	4TB	4TB	
Onboard SAS Expansion Ports	2	2	4	4	
Onboard 1GbE Ports	8	8	0	0	
Onboard 10 GbE Ports (SFP+)	0	0	8	8	
Max. Host Board Slots	2	4	4	4	
Max. Expansion Board	0	2	2	2	
	Note: The expansion board can only be installed in the HB2 slot and has 12Gb/s SAS x 2 ports only connectable with expansion enclosures.				
Host Board Options	16Gb/s FC x 4 32Gb/s FC x 2 1GbE (RJ-45) x 4 10GbE (SFP+) x 2 10GbE (RJ-45) x 2 25GbE (SFP28) x 2 40GbE (QSFP+) x 2 12Gb/s SAS x 2			16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 10GbE (SFP+) x 2 10GbE (RJ-45) x 2 25GbE (SFP28) x 2 40GbE (QSFP+) x 2 12Gb/s SAS x 2	
Note: 1. The two controllers must have identical slot settings. 2. Fibre channel supports point-to-point and switch mode.					
Max. 16Gb/s FC Ports	8	16	16	16	
Max. 32Gb/s FC Ports	4	8	16	16	
Max. 1 GbE Ports	16	24	0	0	
Max. 10GbE Ports (RJ-45)	4	8	8	8	
Max. 10GbE Ports (SFP+)	4	8	16	16	
Max. 25GbE Ports (SFP28)	4	8	8	8	
Max. 40GbE Ports (QSFP+)	4	8	8	8	
Max. 12Gb/s SAS Ports	6	10	12	12	
Expansion Enclosure (JBOD)	JB 3012A, JB 3016A, JB 3024BA, JB 3025BA, JB 3060L			JB 3012A, JB 3016A, JB 3025BA, JB 3060L	
Dimensions (without chassis ears/ protrusions) (W x H x D)	2U 12-bay: 449 x 88 x 500 mm 2U 24-bay: 449 x 88 x 500 mm 2U 25-bay: 449 x 88 x 500 mm			3U 16-bay: 449 x 130 x 500 mm 4U 24-bay: 449 x 174.4 x 500 mm 4U 60-bay: 447.6 x 176 x 840.9 mm	
Package Dimensions (W x H x D)	2U 12-bay: 780 x 379 x 588 mm 2U 24-bay: 780 x 338 x 588 mm 2U 25-bay: 780 x 340 x 588 mm			3U 16-bay: 780 x 423 x 588 mm 4U 24-bay: 780 x 465 x 588 mm 4U 60-bay: 620 x 460 x 1140 mm	
Power Supply Unit (with fan module)	Power Supplies (Redundant/hot-swappable)	460W x 2 (80 PLUS Bronze)	GS 3000/4000: 530W x2 (80 PLUS Bronze) GS 3060L/4060L: 1200W x 2 (80 PLUS Platinum)		
	AC Voltage (with PFC(auto-switching))	100VAC @10A to 240VAC @5A	GS 3000/4000: 100VAC @10A to 240VAC @5A GS 3060L/4060L: 100-127VAC @12.47A, 200-240VAC @7.08A		
	Frequency	50-60 Hz	GS 3000/4000: 50-60 Hz GS 3060L/4060L: 47-63 Hz		
Note: Power is also supplied in redundant mode, allowing full operation with half the resources.					
Safety Standard	<ul style="list-style-type: none"> Electromagnetic Compatibility : CE, BSMI, FCC Safety : UL, BSMI, CB 				

SOFTWARE SPECIFICATIONS

Max. Logical Drives Number	32		
Max. Logical Drives Capacity	512 TB		
Configurable Stripe Size	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, or 1024KB per logical drive		
Configurable Writes Policy	Write-Back or Write-Through per logical drive. This policy can be modified.		
Max. Pool Size	2PB		
Max. Pool Number	32		
Max. Volume Size	2PB		
Max. Volume Number (per pool/per system)	1024		
Max. Host LUN Mapping Number	4096		
Max. Reserved Tag Number per Host-LUN Connection	Up to 256		
Max. iSCSI Initiators (per controller)	832		
Max. Host Connection Number (per FC)	128		
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 30, RAID 50, RAID 60		
Protocol Support	File Level Protocol	CIFS/SMB (Version 2.0/3.0), NFS (Version 2/3/4), AFP (Version 3.1.12), FTP/FXP (vsftp 2.3.4), WebDAV (httpd package 2.4.6)	
	Block Level Protocol	FC, iSCSI, SAS	
	Object Level Protocol	RESTful API	
File Level	Max. File System Size	2PB	
	Max. Number of User Accounts	20000	
	Max. Number of User Groups	512	
	Max. Number of Folder Sharing	2048 (NFS/CIFS/FTP) 255 (AFP)	
	Max. Number of Rsync Jobs	1024	
	Max. Number of Rsync Concurrent Processes	64	
	Max. Number of Concurrent Connections (NFS/CIFS/AFP/FTP)	<ul style="list-style-type: none"> • 16 GB memory: 200 • 32 GB memory: 512 • 64 GB memory: 1024 • 128 GB memory: 2048 	
Management	<ul style="list-style-type: none"> • User account management • Group management • Folder management - folder access control • Quota management 	<ul style="list-style-type: none"> • Integration with Microsoft Active Directory (AD) and LDAP • Folder encryption with AES • Web-based EonOne management software • Storage Resource Management to analyze history records of resource usage 	
Availability and Reliability	<ul style="list-style-type: none"> • Redundant, hot-swappable hardware modules • Device mapper support • Antivirus • Trunk group support 	<ul style="list-style-type: none"> • Cache Safe technology • UPS • WORM (For file level only) • SMB Multichannel 	
Notification	<ul style="list-style-type: none"> • Email 	<ul style="list-style-type: none"> • SNMP traps 	
Applications	<ul style="list-style-type: none"> • File explorer • Proxy server 	<ul style="list-style-type: none"> • Syslog server • VPN server 	<ul style="list-style-type: none"> • LDAP serve • Docker
Cloud Feature	<p>EonCloud Gateway supports the integration with following cloud providers: Amazon S3, Microsoft Azure, Alibaba Cloud, OpenStack, Baidu Cloud, Google Cloud, Tencent Cloud, Wasabi Cloud, etc.</p> <p>For complete information about cloud provides support, please refer to EonCloud Gateway webpage https://www.infortrend.com/global/solutions/eoncloud</p>		
OS Support	<p>Microsoft Windows Server 2019/2016/2012R2/2012/2008R2/2008, Windows 7 SP1, Windows 8.1, Microsoft Windows Hyper-V, Ret Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, VMware, Citrix XenServer, OpenStack Cinder</p>		
	<p>Note: For OS version support, please refer to the compatibility matrix.</p>		

DATA SERVICE

Self-encrypting Drives	Unique factory encryption secures data plus makes deletion simple and complete
Thin Provisioning (Block-Level) (default included)	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space
Local Replication	Snapshot
	Snapshot images per source volume Standard License: 64 / Advanced License: 256
	Snapshot images per pool Standard License: 128 / Advanced License: 4096
	Volume Copy/Mirror
Replication pairs per source volume Standard License: 4 / Advanced License: 8	Replication pairs per system Standard License: 16 / Advanced License: 256
	Note: Standard license is included by default and advanced is an optional license
Remote Replication (Block level)(optional)	Replication pairs per source volume: 8
	Replication pairs per system: 64
	Note: 1. The maximum number of replication pair per source volume is up to 8, regardless of remote asynchronous/remote synchronous/local volume pairs. 2. 4 x 16Gb FC and 2/4 x 32Gb FC host boards do not support Remote Replication.
Remote Replication (File Level)	Support Rsync with 128-bit SSH encryption
Automated Storage Tiering (optional)	2 or 4 storage tiers based on drive types
	SSD supports
	Automated data migration with scheduling options
SSD Cache(optional)	Accelerating data access for random read-intensive environments, such as OLTP
	Supports up to four SSDs per controller
	Recommended DIMM capacity per controller for SSD Cache pool for GS 1000 Gen2, GS 2000
	DRAM:8GB Max SSD Cache Pool Size: 400GB
	DRAM:16GB Max SSD Cache Pool Size: 600GB
	DRAM:32GB Max SSD Cache Pool Size: 1,000GB
	Recommended DIMM capacity per controller for SSD Cache pool for GS 3000/4000 Gen2
	DRAM:8GB Max SSD Cache Pool Size: 500GB
	DRAM:16GB Max SSD Cache Pool Size: 1,000GB
	DRAM:32GB Max SSD Cache Pool Size: 2,000GB
DRAM:64GB and up Max SSD Cache Pool Size: 4,000GB	

WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	Warranty extension: Can extended standard service up to 5 years The following Service can be upgraded to 5 years <ul style="list-style-type: none"> • Upgrade: Replacement part dispatch on the next business day • Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day • Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
	Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status
		Note: Options may vary by region. For more details, please contact our sales representatives.

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com

