



Surveillance Management

Thecus Surveillance Center provides a smooth and intuitive user experience while role-based provides permissions contro access management which allows administrators to create user and administrator profiles according to their responsibilities.



Home Media Center

With the Plex Media Server installed on your Thecus NAS, various devices on your network (such as your Xbox 360 and mobile devices) can connect to and stream your local and online media. Plex makes it easy to manage and enjoy all of your media on your NAS.



Reliable Data Protection

Thecus backup solution allows users to back up files instantly to their NAS, external hard drive, or remote NAS. Whenever a need arises, users can simply go back and recover files quickly and effortlessly.















File Center

Cloud Service Backup Mobile Access

Backup Solution

Download Server

N2350/N4350

Specifications

Hardware Platform

Processor

- · Marvell Armada 385 Dual Core 1GHz SoC (N2350)
- · Marvell Armada 388 Dual Core 1.8GHz (N4350)

System Memory

1GB DDR4

LAN Interface (PCI-e)

- RJ-45x1: 10/100/1000 BASE-TX Auto
- · WOL supported

USB Interface

• USB 3.0 port x2 (back x2)

Disk Interface

- 2 x SATA for internal (N2350)
- 4 x SATA for internal (N4350)
- Support SATA II / SATA III hard disk

Power Supply

- · 40W external power adaptor (N2350)
- 60W external power adaptor (N4350)

System Clock

· Battery-backed up system clock

Buttons

- Power button
- USB copy button
- · Reset button (Reset to factory default)

Environment

- Temperature: 5°C to 40°C
- Humidity: 0 ~ 80 % R.H. (Non-condensing)

- · 2bays Tower (N2350)
- 4-bay Tower (N4350)

Dimensions (HxWxD)

- 135 x 97 x 207 (mm) /5.33 x 3.83 x 8.14 (in)(N2350)
- 135 x 170 x 217 (mm)/ 5.33 x 6.69 x 8.54(in) (N4350)

Weight

- 0.79 kg (N2350)
- 3 kg (N4350)

Certificates

- · CE/FCC/C-Tick/VCCI/BSMI
- · RoHS

Software Functions -

- RAID Modes (N2350): RAID 0, 1 and JBOD
- RAID Modes (N4350): RAID 0, 1, 5, 6, 10 and JBOD
- · Auto-rebuild: Supported
- · Hot-swap: Supported
- · Hot Spare: Supported
- RAID Expansion: Supported

- · Power Management:
- Available spin-down while idle setting
- Bad Block Scanning: Supported
- · SMART Info: Supported
- · SMART Test: Supported
- · Disk Roaming: Supports volume-based roaming to other Thecus NAS (OS7)
- · Disk Wipe and Clone: Supported
- · Secure Disk: Supported

Network

- · Configuration: Fixed IP address, dynamic IP address
- Transport Protocols: TCP/IP, AppleTalk
- File Protocols: SMB/CIFS, HTTP/HTTPS, FTP, NFS v4, AFP
- TCP/IP: IPV6 & IPV4
- DDNS: Supported
- SSH: Supported
- UPnP: Supported
- UPnP Port forwarding: Supported
- Bonjour: Supported
- · VPN Server: Supported
- · vLan: Supported

System Status

- · System Monitor: Monitoring CPU, Memory, Temperature, fan, network utilization and protocols access user count
- · Syslog Management:
- 1. Send syslog to assigned location
- 2. Act as syslog server to receive log info from other systems

Data Access

- Client OS Support :
- Windows XP and after

Windows Server 2003 and after

Mac OS X / Linux

- FTP: Built-in FTP server with bandwidth control
- Secure FTP:

Built-in secure FTP server with bandwidth control

Users can download and upload files with TFTP programs

- Download Manager:
- BT download (via Transmission Module)
- · WebDAV/WebDAV SSL: Supported
- · Printer Server (IPP):
 - 1. Supports USB printers
- 2. Supports a wide range of IPP printers
- 3. Client can manage print tasks (list/delete) via web user interface

Data Backup

- Local folder/iSCSI Backup: Supported
- · Remote folder/iSCSI Backup: Supported
- · Mac OS X Time Machine: Supported
- System Failover: Supported

- iSCSI Target/Initiator: Supports Microsoft/Mac OS X/ Linux initiators and Thecus NAS targets
- iSCSI Thin Provisioning: Supported

Power Management

Scheduled Power On/Off: Supported

Volume Management

- Multiple RAID (N4350): Supported
- Multiple File System Selectable: EXT4/XFS

Multimedia Support

- iTunes Server: Supports AAC, MP3 w/ID3 tag and WAV
- · Media Server: Supports uPnP AV streaming protocol (via Module)

User Authentication

- · Local User: Supports built-in user accounts
- · Local Group: Supports built-in user groups
- Windows ADS: Supported
- LDAP: Supported
- · Access Guard: Supports Black & White list / IP Filter

User Profile

- · Photo Center: Supported
- · File Center: Supported
- · APP Center: Supported
- · Surveillance Center: Supported

Cloud Backup

· Amazon S3: Supported

File System

- · Type: Journaling File System
- · Language Support: Unicode Support
- · Authorization (ACL): "Read", "write", or "deny" privileges to individual users or groups in folders and sub-folders
- User Quota: Supported

Administration

- User Interface: Web-based user interface supports English, Traditional Chinese, Simplified Chinese, Japanese, French, German, Italian, Spanish, Russian
- Utility Program:

MS Windows Setup Wizard

Supports Windows XP and after

Windows Server 2003 and after

Mac OS X Setup Wizard

- · Email Notifications: Sends system messages via email to the system administrator
- · SNMP Trap: Sends system information trap out
- P2P Connection: Mail or FB account to register

Mobile Applications (iOS/Android)

- Thecus Connect (Android):
- Mobile monitoring and administration

File Explore, Webcam monitoring via P2P connection

· Orbweb.me:

- Others • Recycling Bin: Supported
- ISO Mount: Supported

Email: sales@thecus.com

Official Website: www.thecus.com For Windows NAS: wss.thecus.com

Reseller Center: www.thecus.com/reseller_index.php NAS App Center: www.thecus.com/sp_app_center.php Facebook: www.facebook.com/Thecus

Forum: forum.thecus.com Twitter: twitter.com/Thecus_Storage

Blog: blog.thecus.com

RSS: www.thecus.com/rss_news.php YouTube: www.voutube.com/thecusstorage

Design and specifications are subject to change without prior notice. Copyright © 2017 Thecus Technology Corp. All rights reserved.

Retail/Reseller Information













